

HA694 - KIRLOSKAR Air cooled engines for Generating Sets

Key Features

- · Designed for heavy duty applications
- · Extremely reliable.
- · Lower operating cost.
- Easy maintenance higher uptime.
- All service points like dipstick, lube oil filling, lube oil filter, fuel pump, injectors are on one side which is the cooler side. This adds to operator comfort.
- Ideally suitable for Telecom, Services, Residential application etc.
- Superior design standards that minimize power deration even at high ambient temperatures.



Above shown image is for illustration purpose actual product may be different

	En
Engine Make	Kirloskar
Engine Model	HA694
Number of Cylinders	6
Configuration	Inline
Туре	Four stroke
Bore x Stroke (mm)	100 x 120
Displacement (cc)	5652
Cooling	Air cooled
Aspiration	Naturally Aspirated
Compression Ratio	18:1

Direction of Rotation	CCW from flywheel end	
Gross Prime Power KW (hp) at 1500 rpm as per ISO 3046	47.8 (65.0)	
Fuel consumption at 100%load (lit/hr)	13.3	
Fuel consumption at 75%load (lit/hr)	10.02	
Fuel consumption readings are based on diesel fuel with a specific gravity of 0.85 and confirming to BS 2869, Class A2 with +5% tolerance)		
Lube Oil Used	SAE 15W40, API CI4	
Lube Oil Sump Capacity (lit)	15.5	
Starting Method	Electric (12V)	
Dimensions in mm (L x W x H)	1145 x 704 x 922	
Net Weight in kg (dry)	470	

KIRLOSKAR OIL ENGINES LIMITED

gine Specifications

Head Office: Laxmanrao Kirloskar Road, Khadki, Pune 411 003, India. Tel.: +91 20 2581 0341 / 534 Fax: +91 20 2581 3208 Website: www.koel.co.in

KIRLOSKAR DMCC

JBC-5, Cluster W, Jumeirah Lake Towers, P.O.Box 37745, Dubai. U.A.E Tel.: +971 4 443 8591 Fax: +971 4 441 4532

Email: enquiry@kirloskar.ae Website: www.kirloskar.ae

Kirloskar Oil Engines Limited reserved the right to change the design or specifications without notice. Contact your local distributor for more details



