



Enriching Lives

KIRLOSKAR OIL ENGINES LIMITED

A Kirloskar Group Company

G DRIVE DIESEL ENGINES

Model		DV12ETAG12
Standby Power (ESP)	hp / kWm	990 / 728
Prime Power (PRP)	hp / kWm	900 / 662
Suitable for Standby Power (ESP)	kVA / kWe	825 / 660
Suitable for Prime Power (PRP)	kVA / kWe	750 / 600
RPM		1800

Ratings are gross as per ISO3046 and ISO8528-1; refer page 3 for definitions. Assumed power factor is 0.8.



Liquid Cooled

Note: Above picture shown for illustration purpose only, actual product may be different.



Engine Specifications

Physical Data		Air System		
Engine rpm	1800	Air filter type	Dry replaceable	
Cylinders / Configuration	12 / V	Air volume required for combustion (m ³ /hr)	TBA	
Type	Four stroke	Air volume required for cooling (m ³ /hr)	TBA	
Bore x Stroke (mm)	130 x 150			
Displacement (L)	23.88			
Cooling	Liquid cooled			
Aspiration	Turbocharged aftercooled	Cooling System		
Compression ratio	---	Cooling package	Radiator cooled	
Piston speed (m/s)	9.0	Coolant type	Ethylene glycol based premixed with water in ratio 50:50, antifreeze & anti corrosion type	
Fuel consumption Prime power output (L/h) ¹	50%	85		
	75%	118		
	100%	159	Radiator fan load (hp)	30
	110%	176	Cooling system capacity (L)	166

Fuel System		Exhaust System	
Type of fuel filter	Two stage spin on type	Exhaust gas flow rate (kg/hr)	TBA
Governor type	Electronic	Maximum exhaust gas temperature (°C)	580
Class of governing	ISO 8528-5, Class G2	Max. allowed back pressure (mm of Hg)	50
Recommended Fuel	Class A2, High speed diesel		
Fuel supply	Energized to run		

Electrical System		Lubrication System	
Starting arrangement	24V Electric	Type of lube oil filter	Full flow spin on type
Recommended Starter battery capacity	2 x 200Ah	Oil to be used	SAE 15W40 API:CI4
Battery charging alternator	Engine mounted 24V	Oil pump type	Through G-rotor gear pump
Battery charging alternator	55A	Lube oil sump capacity (L) refill / first fill	50 / 53
		Lube oil consumption	0.3% of fuel consumption

1. +5% production tolerance is applicable as per ISO3046. Fuel consumption is based on diesel fuel with a specific gravity of 0.85 and conforming to BS 2869, Class A2) and standard alternator efficiency. The fuel consumption may vary depending upon the alternator efficiency.



Standard and Optional Features

Standard ²	Optional
Diesel engine with radiator	Lube oil drain pump
SAE1 housing adaptor	Water separator
SAE14 flywheel	Sensor mating connector kit
Pusher type fan	Jacket water heater
Engine mounted fuel filter	Exhaust bellow
Engine mounted oil filter	Silencer
Air cleaner	SMF Battery
Rotating parts guard	
Starter motor	
Battery charging alternator	
Oil pressure sensor	
Coolant temperature sensor	
Low coolant level switch	
Instrument panel	
Electronic governor	
Engine wiring harness	

2. Feature and scope of supply may vary please check with KOEL nearest office for the offered scope of supply.

Ratings definitions as per ISO8528:

(De-rating is applicable for climatic conditions other than standard reference conditions of ISO8528-1)

Standby Rating / Emergency Standby power / ESP: These ratings are applicable for supplying electrical power at variable load in the event of a utility power failure. The standby power is maximum power available with no overload permitted on these ratings. The permissible average power output over 24 hours of operation shall not exceed 70% of the ESP. The alternator on this model is peak continuous rated (as defined in ISO 8528-3)

Prime Rating / PRP: These ratings are applicable for supplying continuous electrical power at variable load in lieu of commercial purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours. The permissible average power output over 24 hours of operation shall not exceed 70% of the PRP.

Continuous Rating / COP: These ratings are applicable for supplying power continuously to a constant load up to the maximum output rating for unlimited hours. No sustained overload capability is available for this rating.

Weight & Dimensions

			With radiator
Overall dimensions ³	Length x Width x Height	mm	2840 x 1704 x 1175
Weight ⁴	Gross	kg	4410
	Net	kg	3780

3. Dimensions are for logistics purpose only. Please refer installation / GA drawing for installation.

4. Weight mentioned is indicative only. Actual weight may vary based on configuration.

KIRLOSKAR OIL ENGINES LIMITED

A Kirloskar Group Company

Head Office: Laxmanrao Kirloskar Road, Khadki, Pune 411 003, India.

Tel.: +91 20 2581 0341 / 534 Fax: +91 20 2581 3208 Website: www.koel.co.in

International business office:

KIRLOSKAR DMCC

JBC-5, Cluster W, Jumeirah Lake Towers,
P. O .Box 37745, Dubai. U.A.E
Tel.: +971 4 443 8591
Fax: +971 4 441 4532
Email: enquiry@kirloskar.ae
Website: www.kirloskarib.com

KIRLOSKAR KENYA LTD.

P.O. Box 60061, Off Dunga Road, Nairobi,
Kenya. Tel.: +254 20 653 6632
Fax: +254 20 653 3390
Email: Raj.Patil@kirloskar.com

THE REP. OFFICE OF KIRLOSKAR

Suite 1331A, 13th Floor, Level One Saigon,
mPlaza Saigon,
No. 39 Le Duan Street, Ben Nghe Ward,
District 1, Ho Chi Minh City,
Vietnam Tel.: +84 77 9659756
Email: Sanjay.Kunchetti@kirloskar.com

KIRLOSKAR TRADING SA(PTY) LTD

Unit B1, The Stables Business Park, Cnr of
Third Avenue & Second Road, Limbro Park,
Modderfontein, Johannesburg.
Tel.: +27(0) 11 553 6900/6903
Email: kirsons@kirloskar.co.za

KIRLOSKAR AMERICAS CORPORATION

33300 Egypt Lane, Suite C300, Magnolia,
TEXAS – 77354, United States
Tel.: +1 346 248 5777
Email: Vinay.Kulkarni@koelamerica.com

Kirloskar Oil Engines Limited reserved the right to change the design or specifications without notice.